



XF1 INTEGRA 180 RACE

TECHNICAL SPECIFICATIONS

Motor	Brose S-Mag 36 Volt, Max power: 250 Watt, Torque: 90 Nm
Battery	Fantic Integra, Lithium Ion, 36 Volt, 630Wh
Display	Brose-Marquardt multifunctional display & push-assistance selection unit
Frame	Aluminium Enduro frame, CNC parts, Sizes: S - M - L
Fork	RockShox Lyric Select+ 29" 180mm
Shock	RockShox SuperDeluxe Coil Select+ T205-65
Groupset	Sram GX e-click Eagle 12-speed
Crankset	FSA Isis 170mm
Cassette	Sram NX Eagle 12-speed 11-50
Chain	Sram NX Eagle 12-speed
Front brake	MAGURA MT7 4-piston - Braking S3 Batfly 220mm disc
Rear brake	MAGURA MT7 4-piston - Braking S3 Batfly 203mm disc
Tires	Maxxis Minion, front DHF 29" x 2.6 - rear DHR II 27.5" x 2.8 T.ready
Wheels	Mavic E-XM - front 29" 32F c28 - rear 27.5" 32F c35 - T.ready
Front hub	Miche XMH 550 SH 110-Boost 32f - 6-hole Red Nipples
Rear hub	Miche XMH 550 SH 148-Boost 32f - 6-hole Red Nipples
Handlebar	FSA GRID Ø35 L.800mm - Rise15
Stem	FSA GRID Ø35 L.35mm
Seatpost	Switch Ø30.9, height-adjustable dropper, S-M(100mm), L(125mm)
Saddle	SelleItalia X-LR Gel Flow