



XF1 INTEGRA 160 RACE

TECHNICAL SPECIFICATIONS

Motor	Brose S-Mag 36 Volt, Max power: 250 Watt, Torque: 90 Nm
Battery	Fantic Integra, Lithium Ion, 36 Volt, 630Wh
Display	Brose-Marquardt multifunctional display & push-assistance selection unit
Frame	Aluminium Enduro frame, CNC parts, Sizes: S - M - L
Fork	RockShox Lyrik Select+ 29" 160mm
Shock	RockShox SuperDeluxe Select+ , T205-60 Air
Groupset	Sram GX e-click Eagle 12-speed
Crankset	FSA Isis 170mm
Cassette	SunRace MX90-W 11-50 - 12-speed - Silver/Red
Chain	Sram NX Eagle 12-speed
Front brake	Sram Code-R 4-piston, Galfer Float Black 203mm 6-hole disc
Rear brake	Sram Code-R 4-piston, Galfer Float Black 203mm 6-hole disc
Tires	Maxxis Minion, front DHF 29" x 2.5 - rear DHR II 27.5" x 2.6 T.ready
Wheels	Mavic E-XA , ASY Straight Pull , front Ø29" c.28 - rear Ø27.5" c.35 - T.Ready
Front Hub	MAVIC 110 mm Boost thru axle 15mm
Rear hub	MAVIC 148 mm Boost thru axle 12mm
Handlebar	FSA Grid Ø35 L.760mm - Rise 15
Stem	FSA Grid Ø35 L.50mm
Seatpost	Switch Ø30.9, height-adjustable dropper, S-M(100mm), L(125mm)
Saddle	SelleItalia X-LR Gel Flow